

READ ALL INSTRUCTIONS BEFORE ASSEMBLY AND USE OF THIS PRODUCT.

KEEP INSTRUCTIONS FOR FUTURE USE

WARNING: READ ALL INSTRUCTIONS BEFORE ASSEMBLING AND USING THE PRODUCT. ALWAYS READ AND FOLLOW ASSEMBLY INSTRUCTIONS FOR EACH PRODUCT USE MODE (BEDSIDE SLEEPER, BASSINET, PLAY YARD/CRIB).

Please read additional warning label sound on the sleeping platform of the babybay[®] bedside sleeper (see diagram below).

> WARNING LABEL ON SLEEPING PLATFORM



WARNING: FAILURE TO FOLLOW THESE WARNINGS AND THE INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.

SUFFOCATION HAZARD Discard all packing materials immediately after opening. Plastic bags and ties may cause suffocation or choking.

BEDSIDE SLEEPER WARNINGS

A bedside sleeper is designed to provide a sleeping area for an infant until he or she begins to push up on hands and knees or approximately 5 months of age. Move your child to another sleeping product when your child reaches this stage.

ENTRAPMENT HAZARD—To prevent death from entrapment, the bedside sleeper must be properly secured to an adult bed using the attachment system.

(1) There must be no more than 1/2 in. (13 mm) gap between bedside sleeper and adult bed.

(2) Check tightness before each use by pulling bedside sleeper in a direction away from adult bed.

(3) If gap exceeds 1/2 in. (13 mm), DO NOT use product. DO NOT fill the gap with pillows, blankets or other items that are suffocation hazards.

Always read and follow assembly instructions for each product use mode (bedside sleeper, bassinet, play yard/non-full-size crib).

Always use ALL required parts for each use mode. Check instruction manual for a list of required parts. Periodically check product for loose, damaged, or missing parts.

Always use attachment system when using in Bedside Sleeper Mode.

WARNING: strangulation hazard: When

Resistance Plate system is not in use, store in a safe place not accessible to children.

WARNING: To avoid death from the infant's neck being caught on the top rail on the side that is next to the adult bed, the top rail must be no higher than the adult bed mattress.

DO NOT use bedside sleeper if any parts are missing, damaged, or broken. Contact babybay for replacement parts and instructional literature if needed. DO NOT substitute parts.

Do not place the babybay near a space heater, open fire or other source of strong heat.

Always read and follow assembly instructions for each product use mode (bedside sleeper, bassinet, play yard, crib).

Assemble product according to manufacturer's instructions for ANY use mode—bedside sleeper as well as the bassinet or play yard modes, or both.

Mattress, Boxsprings & Frame aligned



UNACCEPTABLE BED MATTRESS, BOXSPRING & FRAM E NOT IN-LINE



BASSINET WARNINGS

WARNING: FAILURE TO FOLLOW THESE WARNINGS AND THE INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH. SUFFOCATION HAZARD

Babies have suffocated:

- On pillows, comforters, and extra padding
- In gaps between a wrong-size mattress, or extra padding and product sides
- **NEVER** add soft bedding or padding.
- Use **ONLY** mattress provided by manufacturer.
- Always place baby on back to sleep to reduce the risk of SIDS and suffocation.
- If a sheet is used with the, mattress, use only the one provided by the product manufacturer or one specifically designed

to fit the dimension of the product mattress.

FALL HAZARD: TO HELP PREVENT FALLS, DO NOT USE THIS PRODUCT WHEN THE INFANT BEGINS TO PUSH UP ON HANDS AND KNEES OR HAS REACHED 30LB, WHICHEVER COMES FIRST.

- Strings can cause strangulation! **DO NOT** place items with a string around a child's neck, such as hood strings or pacifier cords. **DO NOT** suspend strings over a bassinet or cradle or attach strings to toys.
- DO NOT use if any part of the babybay is broken, torn, or missing.

Use only the pad provided by babybay. **NEVER** add a pillow, comforter, or another mattress for padding.

If a sheet is used with the pad, use only the one provided by babybay.

To reduce the risk of SIDS, pediatricians recommend healthy infants be placed on their backs to sleep, unless otherwise advised by your physician.

Always remove child from babybay whenever adjusting height or usage mode.

CARE AND MAINTENANCE

babybay: Untreated

Use a clean damp cloth to clean surface of wooden parts. Due to the porous nature of untreated wood avoid using chemicals. Light stains may be removed with a fine grit sandpaper.

babybay: Colored Finishes

Use a clean damp cloth to clean the surface of wooden parts. If you must use a detergent, use a mild baby-safe soap.

Classic, Refief, Tranquility Mattress Pad

☑ Hand Wash Only
 ☑ Hang Dry Only
 ➤ Do Not Bleach
 ➢ Do Not Iron
 Ø Dry Clean OK

Details: Unzip and remove the mattress pad cover (refer to corresponding cover cleaning instructions). To clean the mattress pad core: mix warm water with a mild baby friendly detergent. You may either spot clean with a clean cloth or hand wash. Make sure to rinse with clean water to remove all detergent. To dry: squeeze out excess water and hang dry in an area with plenty of airflow.

6

Jersey and Organic Jersey Sheets

☑ Machine Washable up to 104°F (40°C)
 ☑ Hang Dry Only
 ✗ Do Not Bleach
 ➢ Do Not Iron
 ⑨ Dry Clean OK

Mattress Protector

Machine Washable up to 104°F (40°C)
Hang Dry Only
Do Not Bleach
Do Not Iron
Dry Clean OK

Classic and Crib Mattress Cover

☑ Machine Washable up to 104°F (40°C)
 ☑ Hang Dry Only
 ✗ Do Not Bleach
 ☑ Do Not Iron
 ⑨ Dry Clean OK

Relief and Tranquility Mattress Cover

☑ Machine Washable up to 86°F (30°C)
 ☑ Hang Dry Only
 ✗ Do Not Bleach
 ☑ Do Not Iron
 ⑨ Dry Clean OK

Organizers

Machine Washable up to 104°F (40°C)
 Hang Dry Only
 Do Not Bleach
 Do Not Iron
 Dry Clean OK

Canopies

➡ Hand Wash Only at 104°F (40°C)
➡ Hang Dry Only
➡ Do Not Bleach
➡ Do Not Iron
➡ Dry Clean OK

PARTS LIST AS ILLUSTRATED



0

BUILDING YOUR BABYBAY

 Locate the 3 rail pieces (Parts A, B, C). Position the rails upside down so that the large holes on the bottom of the rails are facing up. (the bottom rails will be highlighted throughout these instructions)



2. Screw the 4 threaded dowels (Part #1117) into parts C and B until they are finger tight. The holes in the dowels should be facing up and down, as shown, if they are not facing up, slightly unscrew the dowel until it is. *(the threaded dowels may be a little loose)*



3. Insert the 4 cross dowels (Part #1116) into parts A and B so the hole in the side of the cross dowel and the hole in the end of the rail are aligned as shown.



4. Connect the rails so the threaded dowels are fully inserted. If the threaded dowels (Part #1117) do not easily fit in their corresponding holes, make sure the cross dowels or threaded dowels have not rotated in their holes.



5. Insert the 4 set screws (Part #1122) into parts A and C into the cross dowels as shown. Use a Phillips screwdriver to turn the set screws clockwise until they are secure (40 in/lbs max). **Do not over tighten.**



6. Place the sleeping platform (Part D) so the large holes on the perimeter face up. Affix each platform block (Part Y) in each of the 4 positions as shown by placing the wood peg into the hole.



7. Secure each of the 4 platform blocks (Part Y) using a screw (Part #1211) and the supplied Allen wrench as shown. Screws should be hand tight (40 in/lbs max). **Do not overtighten.**





8. Place the frame flat on the ground as shown. Position the sleeping platform (Part D) so that the 4 platform blocks (Part Y) face the bottom of the babybay *(end with large holes).*



9. Secure 2 of the frame clamps (Part Z) using a screw (Part #1211) to the platform blocks (Part Y) on the sleeping platform (Part D) using the Allen wrench as shown, (40 in/lbs max). **Do not overtighten.**

Next stand the babybay right side up and secure the other 2 frame clamps on the back of the babybay using the same method. Screws should be finger tight (40 in/lbs max). **Do not overtighten.** (Sleeping platform height will need adjusting later).



10. Insert the safety barrier (Part F) into the top of the sleeping platform by placing the wood peg into the hole. Firmly secure the safety barrier by inserting and tightening 2 screws (Part #1211) from the bottom of the sleeping platform using the Allen wrench as shown. Screws should be hand tight (40 in/lbs.). **Do not overtighten.**



ATTACHING YOUR BABYBAY TO YOUR BED

NOTE: The sleeping platform height must be at least 10 inches below the top rail.



NOTE: Always use the appropriate attachment system when using in bedside sleeper mode.

Fixing Set: Attaching to Top of bed frame

NOTE: The safety barrier must be below the top of parent's mattress.

1. Assemble the following fixing set parts before attaching to babybay. Position the Anchor Arms (#1115) facing down and attach them to the Anchor Clamps (Part H) with the Anchor bolts (#2049) as shown. Make sure to leave the screws a little loose for bed frame attachment and adjustments.



2. Attach the clamps to the fixing sets on the babybay with the Allen wrench as shown, making sure to leave the screws a little loose.



3. Move the babybay next to the bed. Make sure the top of the safety barrier is below the top of the parent's mattress and adjust the sleeping platform height as needed. Place the metal arms over the bed frame. Adjust the length of the arms so the babybay is snug against the bed frame and firmly tighten the wingnuts so the arms will not move (40 in/lbs max). Then firmly tighten the clamps (40 in/lbs max). Adjust as needed.



Fixing Set: Attaching to Bottom of Bed Frame

1. Use the Allen wrench to remove the screw on the side of each fixing set, position the metal arms facing up. Reattach the clamps to the fixing sets making sure to leave the screws a little loose.

174)

2. Move the babybay next to the bed. Make sure the top of the safety barrier is below the top of the parent's mattress and adjust the sleeping platform height as needed. Place the metal arms under the bed frame and adjust the height of the fixing set up as much as the bed frame allows. Then adjust the length of the arms so the babybay is snug against the bed frame and firmly tighten the wingnuts so the arms will not move. Then firmly tighten the clamps. Adjust as needed.

Resistance Plate: Attaching to Bed Frame

NOTE: The safety barrier must be below the top of parent's mattress.

- 1. Move the babybay next to the bed. Make sure the top of the safety barrier is below the top of the parent's mattress and adjust the sleeping platform height as needed.
- 2. Unroll the straps from the resistance plate and lay them across the parent's bed. With the resistance plate on the parent's bed opposite to the babybay, use a sawing motion to slide the straps between the mattress and the boxspring. Use this sawing motion to move the resistance plate directly across from the babybay's desired location. Connect the buckles to the front two rail rods on each side of the babybay.
- 3. Tighten the attachment straps at the strap loops protruding out of the resistance plate on the other side of the parent bed by pulling so that the babybay is pulled tight against the parent's bed. Check tightness of the attachment straps each time you place the baby into the babybay so that there is never a gap between the parent's bed and babybay.

Ð







If you have any questions please call or email babybay USA

info@babybay.us

(844) MY BABYBAY

Hours: 9:00 A.M. to 5:00 P.M. Pacific Standard Time

www.babybay.us





